

# **Material Safety Data Sheet**

# **SuperFine Moly5 EP 2**

# Non-hazardous Substance Non-dangerous Goods

**Issue Date** April, 2014

Status Issued by Harrison Manufacturing

## **COMPANY DETAILS**

**Company Name** Harrison Manufacturing Company Pty Ltd (ABN 50 000 080 946) **Address** 75 Old Pittwater Road BROOKVALE NSW 2100 AUSTRALIA

**Telephone Number** 61 2 8978 1000 **Fax Number** 61 2 9905 0065

**Emergency Phone** 

**Number** 61 2 8978 1000 (9:00am - 5:00pm AEST, Monday to Friday)

# PRODUCT IDENTIFICATION

Product Name SuperFine Moly5 EP 2

**UN Proper Shipping** 

Name None allocated Other Names None listed

Recommended Use High Performance Bearing Grease

# Section 2: HAZARDS IDENTIFICATION

NOHSC Classification Not classified as hazardous according to criteria of NOHSC.

ADG Classification Not classified as a Dangerous Good according to the Australian Code for the

Transport of Dangerous Goods by Road and Rail.

Note: Combustible materials may be classified as Class 9: miscellaneous dangerous goods if transported with flammable materials. See ADG code for

further information.

SUSDP Classification Not Scheduled

Risk Phrases None Safety Phrases None

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Name CAS Proportion Risk Phrases 2,5-bis(n-octyldithio)-1,3,4-thiadiazole 13539-13-4 <1% R20 R36/38

R43

Antimony dialkyldithiocarbamate - <5% R20/22 R51/53

Other ingredients determined not to be hazardous Not required >60% -

## Section 4: FIRST AID MEASURES

**Swallowed** DO NOT induce vomiting. Immediately wash out mouth with water, and then give

plenty of water to drink. Seek medical attention.

**Eye** Rinse eyes immediately with water for at least 15 minutes. In case of irritation,

seek medical advice.

**Skin** Remove all contaminated clothing. Wash gently and thoroughly with water and

non-abrasive soap. Ensure contaminated clothing is washed before re-use or discard. If irritation develops and persists, seek medical attention. Should grease be accidentally injected under the skin no matter how minor, seek IMMEDIATE

medical attention.

**Inhaled** Remove the patient to fresh air. Ensure airways are clear and have qualified

person give oxygen through a facemask if breathing is difficult. If irritation

develops, seek medical attention.

No special facilities required.

First Aid Facilities
Advice to Doctor

Treat symptomatically.

NOTE: High Pressure Applications: Injections under the skin resulting from contact with high pressure, constitutes a major medical emergency. Injuries may not appear serious at first but within a few hours, tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that the high pressure may force the product

considerable distance along tissue.

# Section 5: FIRE FIGHTING MEASURES

Fire/Explosion

Hazard Classified as C2 (Combustible liquid).

stream of water; product will float, possibly re-igniting.

Fire Fighting Precautions

Self-Contained Breathing Apparatus (SCBA) and full protective clothing should be

ons worn.

Flash Point > 24 Hazchem Code Non Hazards from

> 240°C (COC) None allocated

Hazards from Combustion

**Products** Oxides of carbon.

# Section 6: ACCIDENTAL RELEASE MEASURES

Spills Procedure SMALL - 20 LITRES OR LESS

Soak up with inert oil absorbent. Arrange for disposal through an approved facility.

LARGE - GREATER THAN 20 LITRES

Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimise exposure. If possible contain the spill. Place inert absorbent material such as vermiculite, sand or dirt onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste

Management Authority.

## Section 7: HANDLING AND STORAGE

#### **Handling** Repeated or prolonged contact with this material should be avoided in order to

lessen the possibility of skin disorders. It is essential that all who come into contact, maintain high standards of personal hygiene ie. washing hands prior to eating, drinking or going to the toilet. Build-up of mists in the working atmosphere must be prevented.

Misuse of empty containers can be hazardous. Do not cut, weld, heat or drill containers. Residue may ignite with explosive violence if heated sufficiently. Do not pressurise or expose to open flame or heat. Keep container closed and bung in place.

#### Storage Precautions Classified as a combustible substance for storage and handling purposes. Store in

a cool, dry, well-ventilated area, out of direct sunlight. Avoid sparks, flames, and other ignition sources. Store away from incompatible materials such as materials that support combustion (oxidising materials). Reference should be made to Australian Standard AS1940- The storage and handling of flammable and combustible liquids.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC). However, Exposure Standards for constituents are listed below.

| SUBSTANCE         | TWA |       | STEL |       |
|-------------------|-----|-------|------|-------|
|                   | ppm | mg/m³ | ppm  | mg/m³ |
| Oil mist, mineral | -   | 5     | -    | 10    |

Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short-term exposure limit (STEL).

**Biological Limit** 

Values

No biological limit allocated.

**Engineering Control** 

The use of mechanical dilution ventilation is recommended whenever this product is used in a confined space, is heated above ambient temperatures or otherwise to maintain ambient concentration below the recommended threshold exposure limits.

**Respirator Type** 

Avoid breathing vapours or mists. Select and use respirators in accordance with AS/NZS 1715/1716. When vapours are generated, the used of the following is recommended: Half face piece respirator with dust/mist filters. The appropriate filter capacity and respirator type will depend on exposure levels encountered. Chemical safety goggles are recommended. If handled hot, a full face shield

Eye Protection

should be worn.
Use of impervious rubber gloves are recommended.

Glove Type Clothing

Clothing should be suitable to avoid product contacting the skin on a prolonged or

repeated basis.

# Section 9: PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** Grey/Black grease

OdourNegligibleMelting Point> 250°CBoiling PointNot availableVapour PressureNot available

Vapour Density Not available pH Not applicable

Specific Gravity
Flashpoint
Flamm. Limit LEL
Flamm. Limit UEL
Solubility in Water

Approx. 0.9 g/cm³
> 240°C (COC)
Not available
Not available
< 0.1 g/l

# **Other Properties**

**Worked Penetration** 

(x60) @ 25°C 265 - 295

# Section 10: STABILITY AND REACTIVITY

**Stability** Stable under normal conditions of storage and handling.

Conditions to Avoid

s to Avoid None allocated.

Incompatible

Materials Strong oxidising agents.

Hazardous Decomposition

**Products** Oxides of carbon.

Hazardous Reactions No hazardous polymerisation will occur.

## Section 11: TOXICOLOGICAL INFORMATION

**Toxicology** The classification as a carcinogen need not apply in this case as the main

constituents in this product are in accordance with Note L of the NOHSC

Designated List of Hazardous Substances (containing less than 3% DMSO extract

as measured by IP 346).

Acute - Swallowed May cause irritation to the mouth, oesophagus and stomach. Symptoms may

include nausea, vomiting and diarrhoea.

Acute - Eye May cause slight to moderate eye irritation, resulting in redness and stinging.

Acute - Skin May dry and defat the skin, resulting in skin irritation and possible dermatitis.

Grease accidentally injected under the skin can result in local necrosis and tissue

damage.

Acute - Inhaled May cause irritation to the mucous membrane and upper airways, especially if the

material is heated or mists are generated and/or is used in poorly ventilated areas.

Symptoms may include headache, dizziness and nausea.

Chronic Prolonged or repeated contact with this material may result in skin irritation leading

to dermatitis.

# Section 12: ECOLOGICAL INFORMATION

Ecotoxicity
Persistence and
Degradability

No ecotoxicological classifications.

**Degradability**This product is inherently biodegradable. **Mobility**Spillages are unlikely to penetrate the soil.

# Section 13: DISPOSAL CONSIDERATIONS

**Disposal Method** Dispose of waste according to federal, EPA, state and local regulations. Assure

conformity with all applicable regulations.

**Special Disposal** 

**Precautions** None allocated.

# Section 14: TRANSPORT INFORMATION

UN Number None allocated

**UN Proper Shipping** 

Name None allocated

**DG Class** Not classified as a Dangerous Good according to the Australian Code for the

Transport of Dangerous Goods by Road and Rail.

Note: Combustible materials may be classified as Class 9: miscellaneous dangerous goods if transported with flammable materials. See ADG code for

further information.

Packaging Group Hazchem Code Special Transport None allocated None allocated

Precautions None allocated

# Section 15: REGULATORY INFORMATION

AICS All ingredients present on AICS.

# Section 16: OTHER INFORMATION

**Last Revision** April, 2014

Acronyms ABN Australian Business Number

**ACGIH** American Conference of Governmental Industrial Hygienists

ADG Australian Dangerous Goods
AEST Australian Eastern Standard Time

AICS Australian Inventory of Chemical Substances
CAS Chemical Abstacts Service Registry Number

COC Cleveland Open Cup
DG Class Dangerous Goods Class.
EPA Environment Protection Agency

**Hazchem** Code of numbers and letters which gives information to emergency

services.

IP Institute of PetroleumPMCC Pensky-Martens Closed Cup

NOHSC National Occupational Health and Safety Commission
SUSDP Standard for the Uniform Scheduling of Drugs and Poisons

**UN Number** United Nations Number

# **CONTACT POINT**

Contact Technical Manager

**Telephone** 61 2 8978 1000

IMPORTANT DISCLAIMER

All reasonable care has been taken to ensure that the information and advice contained herein are accurate at the time of printing. However, Harrison Manufacturing Co accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice

contained herein.

# **End of MSDS**