



## AGRICULTURE OILS PRISTA® UTTO

### DESCRIPTION AND APPLICATION

The Universal Tractor Transmission Oil **PRISTA® UTTO** is developed to lubricate the transmission, final drive/s, wet brakes & clutches, and the hydraulic system/s of farm tractors and other machinery currently in service.

**PRISTA® UTTO** is also recommended for the latest makes and models of farm tractors and off-high way machines and equipment. It is especially engineered to meet the shear stability requirements imposed by Massey Ferguson specification M 1143.

**PRISTA® UTTO** is formulated with selected high quality solvent refined and hydrotreated base stocks, and a specially designed performance additive package to ensure the conformance with lubrication requirements of transmissions/gear boxes, differentials/final drives, wet brakes & clutches and hydraulic systems.

### SPECIFICATIONS

API	GL-4
SAE J 306	80W
SAE J 300	10W-30
John Deere	J20C/J20D
Massey Ferguson	M 1135, M 1134, M 1145, M 1141, M 1143
CNH MAT	3525, 3505, 3509
Ford ESN	M2C 134D, M2C86-B, M2C86-C
CASE MS	1207/1210

### TYPICAL CHARACTERISTICS

PARAMETERS	TEST METHOD	TYPICAL VALUES
Density at 20°C, g/ml	EN ISO 3675	0.880
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	EN ISO 3104	11.6
Kinematic Viscosity 40°C, mm <sup>2</sup> /s	EN ISO 3104	74.3
Viscosity Index	ISO 2909	150
Brookfield apparent viscosity at - 18°C, cP	ASTM D 2983	100 000
Flash Point, COC, °C	EN ISO 2592	195
Pour point, °C	ISO 3016	-39
Copper Strip Corrosion, bala	ISO 2160	1a
Foaming, ml (Tend/Stab)	ISO 6247	
- Seq I, at 24°C		0/0
- Seq II, at 93.5°C		0/0
- Seq III, at 24°C		0/0

**Remark:** The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

ZF-TE-ML	03E/05F/06K/17E
VCE	WB 101
KUBOTA	UDT FLUID
Allison	C-4
FNHA	2-C-200.00
Caterpillar	TO-2

### BENEFITS

- Very good anti-wear, anti-scuffing and anti-seizure properties
- Excellent thermal, oxidation and shear stability
- Very good seal compatibility
- Dependable rust and corrosion protection
- Supreme noise control in the wet brakes

### HEALTH, SAFETY, TRANSPORT AND STORAGE

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

Material safety data sheet is available on [www.prista-oil.com](http://www.prista-oil.com)

### PACKAGES

20L, 210L, 1000L, Bulk