



AGRICULTURE OILS PRISTA® STOU

DESCRIPTION and APPLICATION

PRISTA® STOU oils are unique thanks to their extensive and diverse lubricating properties. These oils are developed to lubricate the engine, transmission, final drive/s, wet brakes, clutches, and hydraulic system/s of farm tractors and equipment currently in service.

PRISTA® STOU oils are recommended for some off-highway construction vehicles and equipment, too.

The Super Tractor Oils Universal **PRISTA® STOU** are unique products formulated with selected high quality solvent refined and hydrotreated base stocks, and a specially designed intricate performance additive package to impart to the finished lubricants all those complex properties, required by STOU oils.

SPECIFICATIONS

ACEA	E2
API	CF-4/SF GL-4
John Deere	JDM J27D
Massey Ferguson	CMS M1139, CMS M 1145, CMS M 1144
Ford	M2C 159B

Allison	C-4
Caterpillar	TO-2
ZF TE ML	06B, 06C, 06D, 07B
MIL-L	2104D
MB	228.1, 227.1

BENEFITS

- Safeguard the engine cleanliness
- Excellent anti-wear, anti-scuffing and anti-seizure properties
- Supreme thermal, oxidation and shear stability
- Very good compatibility with all types of utilized seals
- Reduce the products that have to be kept in stock and eliminate the possibility of erroneous application of lubricants in different units

HEALTH, SAFETY, TRANSPORT AND STORAGE

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

Material safety data sheet is available on www.prista-oil.com

PACKING

20L, 210L, 1000L, Bulk

TYPICAL CHARACTERISTICS

PARAMETERS	TEST METHODS	TYPICAL VALUES		
		10W-30	10W-40	15W-40
Density at 20°C, g/ml	EN ISO 3675	0.875	0.876	0.885
Kinematic viscosity at 100°C, mm ² /s	EN ISO 3104	9.7	14.2	14.9
Kinematic viscosity at 40°C, mm ² /s	EN ISO 3104	61.8	94.3	110.3
Viscosity Index	ISO 2909	140	155	140
Apparent Viscosity (CCS) - at minus 25°C, mPa.s - at minus 20°C, mPa.s	ASTM D 5293	6000 -	6500 -	- 5200
Flas Point, COC, °C	EN ISO 2592	224	228	228
Pour Point, °C	ISO 3016	-33	-33	-30
TBN, HClO ₄ , mg KOH/g	ASTM D 2896	11.6	11.6	11.6

Remark: The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

46, Treti Mart Street 7000 Ruse, Bulgaria

www.prista-oil.com

Ver.2013-01-01