

## Product Information

# SERVOL FUEL EFFICIENT 10W/30

---

## Description

Servol Fuel Efficient 10W/30 is manufactured from high quality mineral oils and a carefully balanced additive system. This grade is suitable for use in petrol and diesel engines and their turbocharged versions fitted to a variety of vehicles. Servol Fuel Efficient 10W/30 provides a high level of engine cleanliness and controls high temperature deposits, especially in turbocharged units. This grade will protect critical components, such as camshafts, valve gear and bearings from wear and ensures overall protection from rust and corrosion.

This multigrade provides excellent cold starting characteristics, increased engine efficiency and fuel economy.

## Applications

Servol Fuel Efficient 10W/30 is recommended for use in passenger cars and light commercial vehicles, including models manufactured by Chrysler, Daewoo, Ford, Isuzu, Kia, Lexus, Mazda, MG Rover, Mitsubishi, Morgan, Nissan, Saab, Suzuki, Toyota, Vauxhall, Volvo, etc. Servol Fuel Efficient 10W/30 can also be used in agricultural, horticultural and off-highway equipment where a grade of this performance level and viscosity grade is specified.

## Performance Levels

API SL / CF  
ACEA A3 / B4  
MB 229.1  
VW 505.00

## Physical Characteristics

Density at 15 °C	0.879
Kinematic Viscosity at 100 °C, cSt.	11.3
Kinematic Viscosity at 40 °C, cSt.	79
Viscosity Index	130
Flash Point (Closed) °C	190
TBN, mg/KOH/g	10.0
Sulphated Ash, %Wt.	1.2
Pour Point, °C	-40



Certificate No. FM 21756  
BS EN ISO9001 2000

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire SY1 2EL

Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044  
BS EN ISO14001 1996